

# PIPE SIZES AND DIMENSIONS



**NO-DIG® Pipes Meet the following requirements:**

- American English Microtunneling Standard C-1208
- American Metric Microtunneling Standard C-1208M
- European Microtunneling Standard EN 295-7
- ✓ **Design assistance, engineering articles and draft specifications available**
- ✓ **1-meter and 2-meter lengths**  
Call for other available lengths
- ✓ **316 stainless steel collars**
- ✓ **Videos and seminars available**

NO-DIG SPECIFICATIONS					
Nominal I.D.	*Nominal O.D.	Approx. Weight per foot	**Allowable Safe Jacking Load in tons		
			2.5 SF	3.0 SF	3.5 SF
8"	11.00	41#	45	38	32
10"	13.50	65#	65	54	47
12"	15.62	78#	83	69	59
15"	19.50	106#	121	101	87
16"(400mm)	21.50	125#	161	134	115
18"	22.12	133#	154	128	110
20"(500mm)	24.50	180#	196	163	140
21"	24.50	158#	163	136	116
24" RW***	28.75	200#	221	184	158
24" TW***	30.25	229#	249	207	178
27"	31.88	260#	258	215	184
30"	35.25	310#	337	281	241
33"	39.00	369#	447	373	320
36"	42.50	420#	463	386	331

\*Pipe O.D. not precision ground surface O.D. \*\*SF designates Safety Factor (3 choices illustrated) @ 7000 psi compressive strength. \*\*\*RW designates Regular Wall, TW designates Thick Wall. NOTE: All dimensions nominal. Latest revisions available as shop drawings.



**1-800-835-0320**

[www.no-dig-pipe.com](http://www.no-dig-pipe.com)



**MISSION CLAY PRODUCTS**

A Division of MCP Industries, Inc.

MANUFACTURERS OF VITRIFIED CLAY PIPE